

5-25kW On-grid Inverter

OGT-5/6/8/10/12/20/25K

OGT-8/10/12/15K-P

98.6%

Max. Efficiency

15A

PV Input Current

180V

Start-up Voltage

Three-Phase

Residential

Commercial

Optimal Power



- 98.6% Max. Efficiency

- 15A PV input current per string, 2-3 MPP trackers

Strong Load



- 180V Start-up Voltage, longer working hours with low start-up voltage

Convenient Installation & Operation



- Plug & Play terminals for easy wiring

- OLED display and App for setting and data management

Flexible Design & Use



- IP66 for indoor and outdoor installation

- Compact size and elegant appearance

Integ O Series

The power operator

 sales@solinteg.com

www.solinteg.com

Model	OGT-5K	OGT-6K	OGT-8K (OGT-8K-P)	OGT-10K (OGT-10K-P)	OGT-12K (OGT-12K-P)	OGT-15K-P	OGT-20K	OGT-25K			
PV Input											
Start-up Voltage [V]	180	180	180	180	180	180	180	180			
Max. DC Input Voltage* [V]	1100*	1100*	1100*	1100*	1100*	1100*	1100*	1100*			
Rated DC Input Voltage [V]	620	620	620	620	620	620	620	620			
Operating voltage range* [V]	160-950*	160-950*	160-950*	160-950*	160-950*	160-950*	160-950*	160-950*			
No. of MPP Trackers	2	2	2; (3)	2; (3)	3	3	3	3			
No. of DC Inputs per MPPT	1/1	1/1	1/1; (1/1/1)	1/1; (1/1/1)	1/1/1; (1/1/2)	1/1/2	1/1/2	1/1/2			
Max. Input Current [A]	15/15	15/15	15/15; (15/15/15)	15/15; (15/15/15)	15/15/15; (15/15/30)	15/15/30	15/15/30	15/15/30			
Max. Short-circuit Current [A]	20/20	20/20	20/20; (20/20/20)	20/20; (20/20/20)	20/20/20; (20/20/40)	20/20/40	20/20/40	20/20/40			
Grid Side											
Rated Output Power [kW]	5.0	6.0	8.0	10.0	12.0	15.0	20.0	25.0			
Max. Output apparent Power [kVA]	5.0	6.0	8.0	10.0	12.0	15.0	20.0	25.0			
Rated AC Voltage	3L/N/PE; 220/380V; 230/400V; 240/415V										
Rated AC Frequency [Hz]	50/60										
Rated Output Current [A]	7.6/7.2/6.9	9.1/8.7/8.3	12.1/11.6/11.1	15.2/14.5/13.9	18.2/17.4/16.7	22.7/21.7/20.8	30.3/29.0/27.8	37.9/36.2/34.7			
Max. Output Current [A]	7.6	9.1	12.1	15.2	18.2	22.7	30.3	37.9			
Power Factor	0.8 leading ... 0.8 lagging										
Max. Total Harmonic Distortion	<3% @Rated output power										
DCI	<0.5%In										
Efficiency											
Max. Efficiency	98.1%	98.3%	98.3%	98.6%	98.6%	98.6%	98.6%	98.6%			
European Efficiency	97.9%	98.0%	98.0%	98.2%	98.2%	98.2%	98.2%	98.2%			
MPPT Efficiency	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%			
Protection											
DC Reverse Polarity Protection	Integrated										
Insulation Resistance Protection	Integrated										
Surge Protection	Integrated										
Over-temperature Protection	Integrated										
Residual Current Protection	Integrated										
Islanding Protection	Integrated (Frequency shift)										
AC Over-voltage Protection	Integrated										
Overload Protection	Integrated										
AC Short-circuit Protection	Integrated										
General Data											
Over Voltage Category	PV: II Main: III										
Dimensions [W×H×D mm]	465x335x200										
Weight [KG]	19	19; (21)	21		24						
Protection Degree	IP66										
Self-Consumption at Night [W]	<1										
Topology	Transformerless										
Operating Temperature Range [°C]	-30~60										
Relative Humidity [%]	0~100										
Operating Altitude [m]	3000 (>3000m derating)										
Cooling	Natural Convection				Natural Convection; (Smart Fan)	Smart Fan					
Noise Level [dB]	<25				<25; (<40)	<40					
Display	OLED & LED										
Communication	RS485, WiFi/LAN/4G (Optional)										

* PV Max. Input voltage is 950V, otherwise inverter will be waiting;